



Specifications Sylvania LED Downlight  
Insaver Slim Aluminium White 1150lm  
70D - 830 Warm White | Cutout  
150mm - IP44 - UGR <19



[View Product](#)

General Information

|                          |                               |
|--------------------------|-------------------------------|
| SKU                      | 255222                        |
| EAN                      | 5410288305004                 |
| Manufacturer Code        | 30500                         |
| Brand                    | Sylvania                      |
| Manufacturer Name        | INSV SL U19 IP44 150 1150 830 |
| Any Lamp all-in warranty | 5 Years                       |
| Average Lifetime (h)     | 100000                        |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x18              |
| Wattage                     | 9.5W              |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                          |                                |
|--------------------------|--------------------------------|
| Light colour options     | Single Color                   |
| Beam Angle (degree)      | 70                             |
| Luminous Flux (Lumen)    | 1150lm                         |
| Luminous Efficacy (lm/W) | 121.1                          |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 150                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 50  |
| Diameter (mm) | 165 |

## Sensor Information

## Why Any-lamp?

Type of sensor

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process